

V-ARMOR SERIES SVEX-PTZ-D1-Z

Explosion-proof PTZ Camera Housing Only



VEILUX[®]
The Art of Surveillance



Features

- Available in either 304 or 306L stainless steel
- Tempered glass window
- Horizontal: 0° - 360° auto tracking
- Vertical: 90° to -90°
- 64/128/255/300 presets
- Integrated wiper system
- Integrated cable

Specifications

CERTIFICATIONS	
Certificate Mark	Exd II C T6 GB/DIP A20 TA, T6
Certificate No	CNEx13.3114
Standards	Q/320412 ZAF046-2013
MECHANICAL	
Housing	Stainless steel 304 or 316L
IP Rating	IP68
Cable Thread Hole	1pcs G3/4 or NPT3/4
Sun Shield	Yes
ELECTRICAL	
Voltage	AC85V~AC265V/DC24V/AC24V
Power	50W /70W (with thermostat)
Surge Protect	TVS 6000V
Optical Fiber Output	Multi mode, or signal mode
AMBIENT	
Ambient Temperature	-25°C to 60°C
Air Pressure	80Kpa to 106Kpa
Relative Humidity	≤95% (no condensation)
PAN AND TILT	
Horizontal	360°
Horizontal Speed	0.1° - 45°/s
Vertical	-90° to +90°
Cruise Scan	Supported
Keep Watch	Supported
Preset	64/128/255/300
Resume Function	Supported
Auto Cruise	Supported
Auto Scan	Supported
GENERAL	
Cable	Integrated cable
Dimensions (LxWxH)	312 x 238 x 350 (mm)/12.3" x 9.4" x 13.8" (in.)
Weight	23kg/50.7lbs
Mounted	Wall, pole

V-ARMOR SERIES SVEX-PTZ-D1-Z

Explosion-proof PTZ Camera Housing Only



VEILUX[®]
The Art of Surveillance

Dimensions

