

# SVEX-Q30ZN

Explosion-Proof PTZ Speed Dome Camera



**VEILUX**<sup>®</sup>  
The Art of Surveillance



## Specifications

CAMERA	
<b>Atmospheric Pressure</b>	80KPa~110Kpa
<b>Ambient Temperature</b>	-20°C~+60°C
<b>Relative Humidity</b>	≤95% (+25°C)
<b>Ex-proof Mark</b>	Exd II CT6 Gb/ Ex tD A21 IP68 T80°C
<b>Explosion Proof Certified</b>	CNEx 15.2504X
<b>Ingress Protection</b>	IP68
<b>Housing Material</b>	Stainless Steel 304 or 316L
<b>Optional Voltage Input</b>	AC24V, AC100~240V
<b>Working Current</b>	≤500mA
<b>Power Consumption</b>	<50w
<b>Pan / Tilt</b>	horizontal rotation: 360° continuous / vertical rotation:-90° to +0°
<b>Rotation Speed</b>	0.1-400°/s
<b>Preset Patrol</b>	128
<b>Control</b>	RS485, PELCO-D/P Protocol
<b>Signal Output</b>	AV output
<b>Cable Output</b>	Integrated cable
<b>Camera Resolution</b>	700TVL
<b>Camera Optical Zoom</b>	36X
<b>Lens</b>	4-92mm
<b>Min. Illumination</b>	Color 0.04lux, B&W 0.004lux
<b>Functions</b>	Auto ICR, Day&night switch
<b>Dimensions</b>	204*204*445mm
<b>Net Weight</b>	12kg
<b>Mount</b>	Wall bracket, Ceiling mount bracket

## Key features

- Stainless steel 304 or 316
- Enclosure Protection: IP6
- Ex II CT6 Gb/ Ex tD A21 IP68 T80 °C
- Fit for gas zone 1, zone 2, dust zone 21, 2
- Optional power input: AC24V, AC100~240
- Working Current: ≤ 500m
- Variable speed:0.1°- 400°/S Pan and Tilt
- Pan : 0-360°, Tilt: -90 to +0°
- Application: gas station, chemical factory, petroleum processing factory, oil drilling platform, marine, pharmaceutical factory, grain storage, winery store

