



VEILUX®

VARI-FOCAL AUTO IRIS LENS (DC DRIVE)

SVL-02812A



SPECIFICATIONS

ITEM	SVL-02812A	
Sensor	CCD	
Format	1/3"	
Mount	CS	
Focal Length	2.8~12mm	
Aperture (F)	1.4~360	
Angle of View	95.6°~22.1°	
Back Focal Length	7.7mm	
M.O.D.	0.1mm	
Effective Aperture	Front Ø28mm	Rear Ø10.2mm
Lens Quantity	12pcs - 9 Groups	
Screw Thread	1" x 1/32" - 6G	
Dimensions	44 x 67.6 x 51.6mm	
Weight	160G	
Color	Black	
Surface Finish	Sand Oxidation	

MATERIAL	
Housing	Aluminium Alloy #6061
Screw	Copper
Lens	Glass Lenses
Lide	Plastic

FEATURES

- Focal Length: 2.8~12mm
- Aperture: 1.4~360
- Mount: CS
- Image Format: 1/3"
- Angle of View: 95.6°~22.1°
- M.O.D.: 0.1m
- Weight: 160g
- Size: Dia. 44 x 67.6 x 51.6mm



VEILUX®

The Art of Surveillance

3015 Eagle Drive, Suite 100, Grand Prairie, Texas 75052
 Local Number: (214) 635-4855 / Fax: (928) 437-6270
sales@veilux.net
www.veilux.net