

VB-2HDIR42V-4N1

2.4 Megapixel 4-in-1 IR Bullet Camera



VEILUX[®]
The Art of Surveillance



Key Features

- Full HD resolution 1920 X 1080 P
- Minimum illumination: 0.003 Lux (AGC ON), 0 Lux IR on
- Support AHD/TVI/CVI/CVBS 4-in-1 signal
- Video output: TVI/AHD/CVI (1080P) & CVBS 960H can be switched freely by OSD
- OSP antioxidant PCB, power/video dual lightning protection design
- OSD menu control through the coax cable (UTC)
- Day/Night (ICR), AWB, AGC, BLC
- 2D/3D-DNR, multi-levels adjustable
- Motion Detection, Privacy Mask, Mirror, Defog, Flip
- 42 pcs small IR array, IR distance 35-40 meters
- 2.8-12mm TDN Electric DC Iris Varifocal Lens
- Aluminum body construction

Specifications	
Image Sensor	1/2.9" 2.4 Mega Pixel Sony CMOS Sensor
Scanning System	Progressive
Resolution	Digital: 1920Hx1080P, 25/30 FPS Analog: 1200 TVL NTSC / PAL
Effective Pixels	1920 (H) X 1080 (V)
Shutter Speed	Auto (1/50(1/60) ~ 1/50,000)
Min. Illumination	0.003 Lux (Color) (0 Lux IR LED ON)
S/N Ratio	>50dB (AGC off)
AGC	Supported (1- 5 Levels)
OSD Menu	Multi languages OSD menu control up to the coaxial cable (UTC)
Day & Night	Auto/ Color/ (B&W)/ Ext (OSD switch)
White Balance	Auto
Backlight	1 - 16 Levels
Mirror	Off/ H/ V/ H&V/ Rotate
HLC	On/ Off
Privacy Zone	2 Areas
Motion	Off/ On
LSC	On/ Off
Language	Info
Day & Night System	ICR
Video Output	Support AHD/TVI/CVI/CVBS 4 in 1 signal
IR Led	42 units
Night View Distance	35-40 Meters
Lens	2.8-12mm TDN Electric DC Iris Varifocal Lens
Power Consumption	DC12V Less than 150mA
Temperature Operating	-4°F to 140°F (-20°C to 60°C)
Temperature Storage	-4°F to 140°F (-20°C to 60°C)
Operating Humidity	Less than 95% (non-condensing)
IP Rating	IP66
Dimensions (WxDxH)	2.3" x 3.9" x 2.5" [6cm x 10cm x 6.5cm]
Unit Weight	0.75 lb (0.340 kg)