

VB-5HDIR72Z-4N1

5MP 4-in-1 IR Motorized Lens Bullet Camera



Features

- 5MP resolution
- Motorized lens 2.7mm-13.5mm
- Video output: AHD/TVI/CVI/CVBS
- Supports multiple languages
- D-WDR, BLC, Defog Mode, Day/Night
- OSD menu control through the coax cable (UTC)
- 2D/3D-DNR , Multi-Levels adjustable
- Motion Detection, Privacy Mask , Mirror , Flip
- IR distance 40-50 m
- Aluminum body construction with plastic shade

Specifications

CAMERA	
Image Sensor	1/2.8" High resolution CMOS Sensor NVP2477H + Sony IMX335
Scanning System	Progressive
Video Out	AHD:5M20fps,5M12.5fps,4M25/30fps,4M15fps,2M25/30fps TVI:5M20fps,5M12.5fps,4M25/30fps,4M15fps,2M25/30fps CVI:4M25/30fps,2M25/30fps CVBS:PAL/NTSC
Resolution	5MP, 0.001 Lux (Color) (0 Lux IR LED ON)
Effective Pixels	2560(H) x 1944(V)
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25 - 1/10000Sec; NTSC 1/25 - 1/10000Sec
S/N Ratio	≥52dB
AGC	1-5 Levels
Video Output	AHD/TVI/CVI/CVBS
Reset Button	NO
LENS	
Lens Type	Motorized Lens
Lens	5X IRIS 2.7mm - 13.5mm
NIGHT VISION	
Infrared LED	42pcs LED
Infrared Distance	40-50 Meters
IR Status	Under 5 Lux By CDS
IR Power On	Camera Sensor Auto Control
CAMERA FEATURES	
Day/Night	Auto/Color/B&W/Ext
White Balance	ATW/Mnual/AWC Push
Backlight	1-16 Levels
Mirror	Off/H/V/H&V/Rotate
HLC	On/Off
LSC	On/Off
Day/Night System	ICR
OSD Control	Includes OSD Control
Image Configuration	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR, White Balance, FLK (Flicker Control)
Corridor Pattern	Supported
Defog Mode	Supported
BLC	Supported
WDR	D-WDR

VB-5HDIR72Z-4N1

5MP 4-in-1 IR Motorized Lens Bullet Camera



Privacy Masking	3 Rectangular Zones
Recording Mode	NVR/VMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian, Czech
INTERFACE	
Alarm	/
SD Card Slot	No
RS485	/
GENERAL	
Housing	Metal, IP66
Anti-cut Bracket	Support
IR Cut Filter	Yes
Operation Temperature	-20°C ~ +60°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 350mA
Dimension (WxHxD)	320x 73 x 75 (mm)
Weight	1000g

Dimensions

