

# VBIP-2B-PRO-U

2MP Fixed IR Network Bullet Camera



## Key Features:

- High quality image with 2MP, 1/2.7"CMOS sensor
- 2MP (1920\*1080)@30/25fps; 720P(1280\*720)@30/25fps
- Ultra 265, H.265, H.264, MJPEG
- 120dB true WDR technology enables clear image in strong light scene
- Support 9:16 Corridor Mode
- Built-in Mic
- Smart IR, up to 30m (98ft) IR distance
- Supports 128 G Micro SD card
- Support PoE power supply
- 3-Axis

## Specifications:

CAMERA					
<b>Sensor</b>		1/2.7", 2.0 megapixel, progressive scan, CMOS			
<b>Lens</b>		2.8mm@F2.0			
<b>DORI Distance</b>	<b>Lens (mm)</b>	<b>Detect (m)</b>	<b>Observe (m)</b>	<b>Recognize (m)</b>	<b>Identify (m)</b>
	2.8mm	42	16.8	8.4	4.2
<b>Angle of View (H)</b>		112.9°			
<b>Angle of View (V)</b>		59.1°			
<b>Angle of View (O)</b>		121.2°			
<b>Wide Dynamic Range</b>		Pan: 0° ~ 360°, Tilt: 0° ~ 90°, Rotate: 0° ~ 360°			
<b>Shutter</b>		Auto/Manual, 1 ~ 1/100000s			
<b>Minimum Illumination</b>		Color: 0.01Lux (F2.0, AGC ON) 0 Lux with IR			
<b>Day/Night</b>		IR-cut filter with auto switch (ICR)			
<b>Digital noise reduction</b>		2D/3D DNR			
<b>S/N</b>		> 52dB			
<b>IR Range</b>		Up to 30m (98ft) IR range			
<b>Wavelength</b>		850nm			
<b>IR On/Off Control</b>		Auto/Manual			
<b>Defog</b>		Digital Defog			
<b>WDR</b>		120dB			
VIDEO					
<b>Video Compression</b>		Ultra 265, H.265, H.264, MJPEG			
<b>H.264 code profile</b>		Baseline profile, Main profile, High profile			
<b>Frame Rate</b>		Main Stream: 1080P (1920*1080), Max 30fps; 720P (1280*720), Max 30fps Sub Stream: 720P (1280*720), Max 30fps; D1 (720*576), Max 30fps; 640*360, Max 30fps;			
<b>Video Bit Rate</b>		128 Kbps~6144 kbps			
<b>U-code</b>		Supported			
<b>OSD</b>		Up to 4 OSDs			
<b>PRIVACY MASK</b>		Up to 4 areas			
<b>ROI</b>		Up to 8 areas			
<b>Video stream</b>		Dual streams			
IMAGE					
<b>White Balance</b>		Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2			
<b>Digital Noise Reduction</b>		2D/3D DNR			
<b>Smart IR</b>		Supported			
<b>Flip</b>		Normal/Vertical/Horizontal/180°/90°Clockwise/90°counter-clockwise			
<b>Dewarping</b>		NA			
<b>HLC</b>		Supported			
<b>BLC</b>		Supported			
EVENTS					
<b>Basic Detection</b>		Cross line, intrusion(based on human body detection), motion detection, Ultra motion detection, tampering alarm, audio detection			

# VBIP-2B-PRO-U

2MP Fixed IR Network Bullet Camera



**VEILUX**  
The Art of Surveillance

<b>General Function</b>	Watermark, IP address filtering, access policy, ARP protection, RTSP authentication, user authentication, HTTP authentication
<b>AUDIO</b>	
<b>Audio Compression</b>	G.711U, G.711A
<b>Audio Bitrate</b>	64 Kbps
<b>Two-way Audio</b>	N/A
<b>Suppression</b>	Supported
<b>Sampling Rate</b>	8KHZ
<b>Storage</b>	
<b>Edge Storage</b>	Micro SD, up to 128GB
<b>Network Storage</b>	ANR,NAS(NFS)
<b>NETWORK</b>	
<b>Protocols</b>	IPv4, IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL/TLS, 802.1x, SNMP
<b>Compatible Integration</b>	ONVIF (Profile S, Profile G, Profile T), API , SDK
<b>User/Host</b>	Up to 32 users. 2 user levels: administrator and common user
<b>Client</b>	Guard Station, 2M Station
<b>Web Browser</b>	Plug-in required live view: IE 10 and above, Chrome 45 and above, Firefox 52 and above, Edge 79 and above Web Browser  Plug-in free live view: Chrome 57.0 and above, Firefox 58.0 and above, Edge 16 and above
<b>INTERFACE</b>	
<b>Network</b>	1 * RJ45 10M/100M Base-TX Ethernet
<b>CERTIFICATIONS</b>	
<b>EMC</b>	CE-EMC (EN 55032: 2015+A1:2020,EN 61000-3-3: 2013+A1: 2019,EN IEC 61000-3-2: 2019+A1: 2021,EN 55035: 2017 +A11:2020) FCC (FCC CFR 47 part15 B, ANSI C63.4-2014)
<b>Safety</b>	CE LVD (EN 62368-1:2014+A11:2017) CB (IEC 62368-1:2014) UL (UL 62368-1, 2nd Ed., Issue Date: 2014-12-01)
<b>Environment</b>	CE-RoHS (2011/65/EU;(EU)2015/863); WEEE (2012/19/EU); Reach (Regulation (EC) No 1907/2006)
<b>GENERAL</b>	
<b>Power</b>	DC12V±25%, PoE (IEEE802.3 af) Power consumption: Max 7w
<b>Dimensions (Ø x H)</b>	166 × 63 × 62mm (6.5" × 2.5" × 2.5")
<b>Weight</b>	0.39kg (0.86lb)
<b>Working Environment</b>	-30°C ~ +60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
<b>Storage Environment</b>	-30°C ~ +60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
<b>Surge Protection</b>	4KV
<b>Ingress Protection</b>	IP67
<b>Reset Button</b>	N/A

## Dimensions

