


V-RECON SERIES VD-4HDIR30V-TVI

4.1MP High Definition IR Dome Camera



Key Features

- 1/2.8" 4.1MP Sony CMOS Sensor
- HD Resolution: 2688(H)×1520(V), 4.1MP NTSC/ PAL
- RealWDR
- Motion Detection
- Privacy Mask Function
- 2.8-12mm
- True Day & Night (ICR)
- Video Output-TVI
- Built-in IR LED 30 pcs (Night View Distance Indoor 35m/ Outdoor 25m)
- External Control (Focus/Zoom, OSD)
- Service Video Controller through Cable

Specifications	
Image Sensor	1/2.8" 4.1 Mega Pixel Sony CMOS Sensor
Scanning System	Progressive
Resolution	2688(H)×1520(V), 4.1MP NTSC/ PAL
Shutter Speed	Auto/ Manual (1/50(1/60) ~ 1/100,000)
Min. Illumination	0.5 Lux (Color) (0 Lux IR LED ON)
S/N Ratio	>50dB (AGC off)
AGC	1- 5 Levels
Day & Night	Auto/ Color/ B&W/ Ext
White Balance	ATW/ Manual/ AWC Push
Backlight	1 - 16 Levels
Mirror	Off/ H/ V/ H&V/ Rotate
HLC	On/ Off
Privacy Zone	2 Areas
Motion	Off/ On
LSC	On/ Off
Language	Info
Day & Night System	ICR
Video Output	TVI
IR Led	30 units
Night View Distance	Indoor 35m / Outdoor 25m
Lens	2.8-12mm Varifocal Lens
Power Consumption	DC12V 500 mA
Temperature Operating	14°F to 131°F (-10°C to 55°C)
Temperature Storage	-4°F to 140°F (-20°C to 60°C)
Operating Humidity	10% - 85% RH
IP Rating	IP-54
Dimensions (WxDxH)	Ø5.5" x 4.3"(H) [Ø14cm x 11cm(H)]
Unit Weight	0.851 lb (0.385 kg)
Shipping Weight	1.10 lb (0.498 kg)