

# V-RECON SERIES VD-70MINI-IRV

3 Axis Mini IR Dome Camera



## Key Features

- High Resolution 700 TV Lines
- 0.001@F1.2 (0 Lux IR LED ON)
- 24 IR LEDs
- E-WDR
- EZoom
- Motion Detection
- DIS
- Triple Voltage Optional (12VDC, 24VDC, 24VAC)

Specifications	VD-70MINI-IRV
<b>Sensor</b>	1/3" Sony CCD EFFIO-E
<b>Signal System</b>	NTSC / PAL
<b>Max Pixels</b>	1020(H) x 508(V) (NTSC) 1020(H) x 596(V) (PAL)
<b>Effective Pixels</b>	976(H) x 494(V) (NTSC) 976(H) x 582(V) (PAL)
<b>Sync. System</b>	Internal
<b>Min. Illumination</b>	0.001@F1.2 (0 Lux IR LED ON)
<b>Horizontal Resolution</b>	700TVL
<b>Lens</b>	2.8-12mm Auto Iris Varifocal IR Corrected
<b>Lens (Optional Upgrade)</b>	6-22mm Auto Iris Varifocal IR Corrected
<b>IR LED</b>	24 Units
<b>Video Output Level</b>	1.0Vp-p/75 Ω
<b>S/N</b>	> 52dB(AGC off)
<b>Gain Control</b>	Auto
<b>Back Light Compensation</b>	Back Light Compensation / HSBack Light Compensation
<b>Wide Dynamic Range</b>	Super WDR
<b>White Balance</b>	ATW / USER1 / USER2/ ANTI CR/ Manual / Push Lock / Push ATW
<b>Viewing Angle</b>	Wide: 76.1° x 55.8° (HxV) Tele 23.8° x 17.9° (HxV)
<b>Privacy Mask</b>	4 Windows, (Polygonal, 4 Colors)
<b>ENVIRONMENTAL</b>	
<b>Temperature</b>	Operating: 14°F to 131°F (-10°C to 55°C) Storage: -4°F to 140°F (-20°C to 60°C)
<b>Operating Humidity</b>	10% -85% RH
<b>ELECTRICAL</b>	
<b>Power Supply</b>	12 VDC
<b>Power Consumption</b>	Less than 150mA
<b>PHYSICAL</b>	
<b>Dimensions (W x D x H)</b>	4.3" x 3.5"(H) (in) / 110 x 90 (H) (mm)
<b>Unit Weight</b>	0.50 lb (0.226 kg)
<b>Shipping Weight</b>	0.80lb (0.362 kg)

## Recommended Accessories



- VPS-12810
- VPS-121630