

# ACCESORIES VIPK-PRO

IP Desktop Professional USB desktop controllers

Joystick Performance



Specifications	
<b>Joystick Performance</b>	Hall effect three axes joystick X/Y/Z for positioning control
<b>Joystick Travel</b>	36° for X and Y axes 60° for Z axis
<b>Centering</b>	Single spring, omnidirectional
<b>Joystick shaft</b>	Stainless steel
<b>Joystick boot</b>	Neoprene
<b>Joystick handle</b>	Glass filled nylon
<b>Pushbutton performance</b>	10 tactile pushbuttons on housing Two tactile push-buttons on joystick 3,000,000 cycles
<b>Desktop housing</b>	High impact ABS
<b>Power</b>	Via USB interface (5V DC) Consumption 32mA
<b>Operating conditions</b>	-25°C to +85°C (-13°F to +185°F)
<b>Approvals</b>	EN 55024:1998, EN 55022, CE, FCC Part 15 Subpart B Class B, RoHs compliant
<b>Weight</b>	440 g (0.97lb)
<b>Interface</b>	USB port
<b>Connectors</b>	USB Type A Male Cable Length: 2m; 6ft. 6.8in
<b>Systems support integration</b>	Windows 7, Vista, XP, 2000
<b>Supported protocols</b>	USB HID 1.1 game controller Direct X (Gaming Control) Joystick: Three HID axes Pushbuttons: 12 HID buttons Uses standard DirectX HID drivers Connects directly to workstation PC
<b>Environmental</b>	For indoor use only

## Key Features

- 3 axis joysticks for P/T/Z control
- 10 tactile pushbutton
- Programmable pushbutton switches
- USB 1.1 HID compliant "game controller"
- Easy to use and operate
- Optional programming software

• All values are nominal

## Dimensions

- Dimensions are in mm/(inch)

