

# VL-EXT8231-XXX

Explosion proof Spot Light



## Key Features

- Input Voltage: AC 100-270 v
- PF>0.95 CRI: Ra>75
- Protection Grade: IP66
- Lumen Flux: 120lm/w
- Anti Corrosion: WF2
- Weight: 3.8 kg / 8.3 lbs
- Size: 230 x 166 mm / 9 x 6.5 in
- Beam Angle: 14°
- Ex-proof Grade: ExdIICT6
- Carton Size: 26.6 x 26.7 x 28.6 cm / 10.4 x 10.5 x 11.2 in
- Gross Weight: 4.3 kg / 9.4 lbs

MODEL	VOLTAGE
VL-EXT8231-50W	50W
VL-EXT8231-60W	60W
VL-EXT8231-80W	80W
VL-EXT8231-90W	90W

<b>Rated Voltage</b>	AC220 v
<b>Power</b>	40-80 w
<b>Frequency</b>	50/60 hz
<b>Light Efficiency</b>	120 lm
<b>Power Factor</b>	>0.95 pf
<b>Operating Temperature</b>	-30~50 °C / -22~122 °F
<b>Storage Temperature</b>	-30~50 °C / -22~122 °F
<b>Protection Level</b>	IP66
<b>Lighting Angle</b>	20/60/90 °
<b>Light Source</b>	led
<b>Correlate Color Temperature</b>	3000-6500 k
<b>Color Rendering Index</b>	≥70 ra
<b>LED Qty</b>	80 pcs
<b>Base Specifications</b>	CREE3030
<b>LED'S Operating Life</b>	100000 h
<b>Start-Up Time</b>	≤0.2 s
<b>Anti-Corrosion Grade</b>	WF2
<b>Explosion Proof Grade</b>	ExdIICT6W
<b>Executive Standard</b>	GB3836.1 / GB3836.2
<b>Weight</b>	5.4 kg / 11.9 lbs
<b>Size</b>	230 x 166 mm / 9 x 6.5 in

## Dimensions

