

PRO SERIES VMS-Q

Video Management System



Specifications

CAPACITY	
Maximum Number of Cameras	No limit, recommended no more than 1000 x 3
Maximum Number of Decoder	4 x 128
User	No limit, recommended no more than 64
Roles For Each User	15
RECORDING AND PLAYBACK	
Playback	Support up to 8 channels (Default Synchronous Playback of 4 channels and can be customised to 8 channels)
Function And Feature	Search for videos by time, event, intelligence, support for video downloads, screenshots, multiply playback (1/8 to 16 times), audio
ALARM MANAGEMENT	
Alarm Type	Multiple device alarm types
Alarm Plan	No
Alarm Triggered Action	Alarm triggered actions including live view
Alarm Records	No
VIDEO WALL	
Video wall configuration	no
Video on wall	no
MINIMUM CLIENT WORKSTATION PC REQUIREMENTS	
Operating system	Microsoft Windows 7/Windows 8.1/Windows 10/Windows 11 (32/64 bit, Professional or Enterprise)
CPU	Intel Pentium 4.3.0@3.0 GHz
Memory	2GB
Display adapter	Video memory of 265 MB or higher
Free disk space	Minimum 3GB for single site systems
NIC	Fast ethernet port
Display Resolution	1024 x 768
MINIMUM MANAGEMENT SERVER REQUIREMENTS	
Operating System	Mac OS version 10.5

Features

- No camera limit, but 1000x3 is recommended
- No user limit, but no more than 64 is recommended
- Supports up to 8 channels (Default Synchronous Playback of 4 channels can be customised to 8 channels)
- Alarm triggered actions including live view
- Microsoft Windows 7/Windows 8.1/Windows 10/windows 11 (32/64 bit, Professional or Enterprise)