PRO SERIES VPRO-NVR-32-4H-U



32 Channel Network Video Recorder with 4HDD



Features:

- Support Ultra 265/H.265/H.264 video formats
- 32-channel input
- Support mainstream cameras of ONVIF conformance(Profile S, Profile G, Profile T) and RTSP protocols
- VGA and HDMI independent output
- Up to 16 Megapixels resolution recording
- 4 SATA HDD, up to 8TB for each HDD
- ANR technology to enhance the storage reliability when the network is disconnected
- Support cloud upgrade

Specifications:

VIDEO/AUDIO INPUT		
Video input (IP)	32ch	
Two-way Audio	1-ch, RCA(Using the audio input and output)	
NETWORK		
Incoming Bandwidth	320Mbps	
Outgoing Bandwidth	160Mbps	
Remote Users	128	
Protocols	TCP/IP;P2P;UPnP;NTP;DHCP;PPPoE;HTTP;HTTPS;DNS;DD- NS;SNMP;SMTP;RTSP;80 2.1x;IPV6	
Browser (Plugin)	Windows:IE(IE10/11), Firefox (version 52.0 and above), Chrome(version 45 and above), Edge(version 79 and above)	
VIDEO/AUDIO OUTPUT		
HDMI Output	HDMI:4K (3840x2160)@30, 1920x1080p@60, 1920x1080p@50, 1600x1200@60, 1280x1024@60, 1280x720@60, 1024x768@60	
VGA Output	VGA:1920x1080p@60, 1920x1080p@50, 1280x1024@60, 1600x1200@60, 1280x720@60, 1024x768@60	
RCA Audio Output	1-ch	
Liveview Display	1/4/6/8/9/16/25/32	
Corridor Mode Screen	3/4/5/7/9/10/12/16/32	
DECODING		
Decoding Format	Ultra 265, H.265, H.264	
Decoding Capability	Ultra 265/H.265: 2 x 16MP@30, 2 x 12MP@30, 4 x 4K@30, 6 x 5MP@30, 8 x 4MP@30, 10 x 3MP@30, 16 x 1080P@30, 32 x 960P@25 H.264: 2 x 16MP(4800*2688)@30, 2 x 12MP@30, 2 x 4K@30, 4 x 5MP@30, 6 x 4MP@30, 8 x 3MP@30, 14 x 1080P@30, 30 x 720P@30, 32 x D1	
Audio Compression	G.711A, G.711U	
SNAPSHOT		
FTP/Schedule/Event Snapshot	4-ch snapshot, up to D1 resolution	
RECORDING		
Recording Resolution	16MP/12MP/8MP/6MP/5MP/4MP/3MP/1080P/960P/720P/ D1/2CIF/CIF	
Synchronous Playback in Local	16-ch	
SMART	SMART	
VCA Detection by IPC	Vehicle Detection, Intrusion Detection, Cross Line Detection, Enter Area, Leave Area, Temperature Detection(Fire Detection, Smoking Detection, Temperature Measurement, Smoke and Fire Detection), UMD(Ultra Motion Detection), Video Metadata, Traffic Monitoring	
VCA Search	Motor Vehicle Search; Non-Motor Vehicle Search; Human Body Search; General Search; People Counting Report;	
People Counting	People Flow Counting, Crowd Density Monitoring	
Smart Intrusion Prevention (SIP), Vehicle Detection, UMD, Video Metadata by Camera	8ch	


PRO SERIES VPRO-NVR-32-4H-U

32 Channel Network Video Recorder with 4HDD



Beneral Alarm Defocus Detection; Scene Change Detection; Object Left Behind; Object Removed; Auto Tracking; Motion Detection; Tampering;Hu- man Body Detection; Video Loss; Alarm Input; Audio Detection Alert Alarm IP Conflict; Network Disconnected; Disk Offline; Disk Abnormal; Illegal Access; Hard Disk Space Low; Hard Disk Full; Recording/ Snapshot Abnormal GUI LANGUAGE 38 languages: Simplified Chinese, Traditional Chinese, English, Vietnamese, Thai, Turkish, Spanish (Latin America), Portuguese (Brazil), Spanish, Portuguese, French, German, Italian, Dutch, Polish, Czech, Hungarian, Slovak, Russian, Hebrew, Arabic, Ukrainian, Estonian, Bulgarian, Greek, Romanian, Danish, Swedish, Norwegian, Finnish, Croatian, Slovenia, Serbia, Korean, Japanese, Latvian, Lithuanian, Persian HARD DISK SATA 4 SATA Interfaces Capacity Up to 8TB for each HDD(The maximum HDD capacity varies with environment temperature) EXTERNAL INTERFACE N/A Natarm In 16-ch Alarm In 16-cch Alarm Out 4-cch GENERAL 20% RH (non-condensing) Power Supply 12V DC/5A Working Temperature -10 °C ~ 55 °C (14 °F ~ 131 °F) Working Humidity ≤ 90% RH (non-condensing) Power Consumption (without HDD) ≤ 3.15Kg (6.94lb)	AL ADM		
General Alarm Object Removed; Auto Tracking, Motion Detection, Tampering; Human Body Detection; Video Loss; Alarm Input; Audio Detection Alert Alarm IP Conflict, Network Disconnected; Disk Offline; Disk Abnormal; Illegal Access; Hard Disk Space Low; Hard Disk Full; Recording/ Snapshot Abnormal GUI LANGUAGE 38 languages: Simplified Chinese, Traditional Chinese, English, Vietnamese, Thai, Turkish, Spanish (Latin America), Portuguese (Brazil), Spanish, Portuguese, French, German, Italian, Dutch, Polish, Czech, Hungarian, Stovak, Russian, Hebrew, Arabic, Urkrainain, Estorian, Bulgarian, Greek, Romanian, Danish, Swedish, Norwegian, Finnish, Croatian, Slovak, Russian, Hebrew, Arabic, Urkrainan, Estorian, Greek, Romanian, Danish, Swedish, Norwegian, Finnish, Croatian, Slovak, Russian, Hortey, Japanese, Latvian, Lithuanian, Persian HARD DISK Up to 8TB for each HDD(The maximum HDD capacity varies with environment temperature) EXTERNAL INTERFACE 2 RJ45 10W/100M/1000M self-adaptive Ethernet Interface USB Front: 1 x USB2.0;Rear panel: 1 x USB2.0, 1 x USB3.0 RS485 1 RS232 N/A Alarm In 16-ch Alarm Out 4-ch GENERAL 90% RH (non-condensing) Power Supply 12V DC/5A Working Humidity 90% RH (non-condensing) ≥ 20W Supplexed (self)	ALARM		
Alert Alarm Illegal Access; Hard Disk Space Low; Hard Disk Full; Recording/ Snapshot Abnormal GUI LANGUAGE 38 languages: Simplified Chinese, Traditional Chinese, English, Vietnamese, Thai, Turkish, Spanish (Latin America), Portuguese (Brazil), Spanish, Portuguese, French, German, Italian, Dutch, Polish, Czech, Hungarian, Stovak, Russian, Hebrew, Arabic, Urrainian, Estonian, Bulgarian, Greek, Romanian, Danish, Swedish, Norwegian, Finnish, Croatian, Slovenia, Serbia, Korean, Japanese, Latvian, Lithuanian, Persian HARD DISK 4 SATA Interfaces Capacity Up to 8TB for each HDD(The maximum HDD capacity varies with environment temperature) EXTERNAL INTERFACE 2 RJ45 10M/100M/1000M self-adaptive Ethernet Interface USB Front: 1 x USB2.0;Rear panel: 1 x USB2.0, 1 x USB3.0 RS485 1 RS232 N/A Alarm In 16-ch Alarm Out 4-ch GENERAL -10 °C ~ 55 °C (14 °F ~ 131 °F) Power Supply 12V DC/5A Working Temperature -10 °C ~ 55 °C (14 °F ~ 131 °F) Working Humidity ≤ 90% RH (non-condensing) Power Consumption (without HDD) ≤ 20W	General Alarm	Object Removed; Auto Tracking; Motion Detection; Tampering; Hu-	
38 languages: Simplified Chinese, Traditional Chinese, English, Vietnamese, Thai, Turkish, Spanish (Latin America), Portuguese (Brazil), Spanish, Portuguese, French, German, Italian, Dutch, Polish, Czech, Hungarian, Slovak, Russian, Hebrew, Arabic, Ukrainian, Estonian, Bulgarian, Greek, Romanian, Danish, Swedish, Norwegian, Finnish, Croatian, Slovenia, Serbia, Korean, Japanese, Latvian, Lithuanian, Persian HARD DISK SATA 4 SATA Interfaces Capacity Up to 8TB for each HDD(The maximum HDD capacity varies with environment temperature) EXTERNAL INTERFACE 2 RJ45 10M/100M/1000M self-adaptive Ethernet Interface USB Front: 1 x USB2.0;Rear panel: 1 x USB2.0, 1 x USB3.0 RS485 1 RS232 N/A Alarm In 16-ch Alarm Qut 4-ch GENERAL 12V DC/5A Power Supply 12V DC/5A Working Temperature -10 °C ~ 55 °C (14 °F ~ 131 °F) Working Humidity ≤ 90% RH (non-condensing) Power Consumption ≤ 20W Weight (without HDD) ≤ 3.15Kg (6.94lb)	Alert Alarm	Illegal Access; Hard Disk Space Low; Hard Disk Full; Recording/	
GUI LanguageVietnamese, Thai, Turkish, Spanish (Latin America), Portuguese (Brazil), Spanish, Portuguese, French, German, Italian, Dutch, Polish, Czech, Hungarian, Slovak, Russian, Hebrew, Arabic, Ukrainian, Estonian, Bulgarian, Greek, Romanian, Danish, Swedish, Norwegian, Finnish, Croatian, Slovenia, Serbia, Korean, Japanese, Latvian, Lithuanian, PersianHARD DISKSATA4 SATA InterfacesCapacityUp to 8TB for each HDD(The maximum HDD capacity varies with environment temperature)EXTERNAL INTERFACENetwork Interface2 RJ45 10M/100M/1000M self-adaptive Ethernet InterfaceUSBFront: 1 x USB2.0; Rear panel: 1 x USB2.0, 1 x USB3.0R\$232N/AAlarm Out4-chGENERALPower SupplyPower Supply12V DC/5AWorking Temperature-10 °C ~ 55 °C (14 °F ~ 131 °F)Working Humidity≤ 90% RH (non-condensing)Power Consumption (without HDD)≤ 3.15Kg (6.94lb)	GUI LANGUAGE		
SATA4 SATA InterfacesCapacityUp to 8TB for each HDD(The maximum HDD capacity varies with environment temperature)EXTERNAL INTERFACENetwork Interface2 RJ45 10M/100M/1000M self-adaptive Ethernet InterfaceUSBFront: 1 x USB2.0; Rear panel: 1 x USB2.0, 1 x USB3.0RS4851RS232N/AAlarm In16-chAlarm Out4-chGENERALPower Supply12V DC/5AWorking Temperature-10 °C ~ 55 °C (14 °F ~ 131 °F)Working Humidity \leq 90% RH (non-condensing)Power Consumption (without HDD) \leq 3.15Kg (6.94lb)	GUI Language	Vietnamese, Thai, Turkish, Spanish (Latin America), Portuguese (Brazil), Spanish, Portuguese, French, German, Italian, Dutch, Polish, Czech, Hungarian, Slovak, Russian, Hebrew, Arabic, Ukrainian, Estonian, Bulgarian, Greek, Romanian, Danish, Swedish, Norwegian, Finnish, Croatian, Slovenia, Serbia, Korean, Japanese,	
CapacityUp to 8TB for each HDD(The maximum HDD capacity varies with environment temperature)EXTERNAL INTERFACENetwork Interface2 RJ45 10M/100M/1000M self-adaptive Ethernet InterfaceUSBFront: 1 x USB2.0;Rear panel: 1 x USB2.0, 1 x USB3.0R\$4851R\$232N/AAlarm In16-chAlarm Out4-chGENERALPower Supply12V DC/5AWorking Temperature-10 °C ~ 55 °C (14 °F ~ 131 °F)Working Humidity \leq 90% RH (non-condensing)Power Consumption (without HDD) \leq 3.15Kg (6.94lb)	HARD DISK		
Capacityenvironment temperature)EXTERNAL INTERFACENetwork Interface2 RJ45 10M/100M/1000M self-adaptive Ethernet InterfaceUSBFront: 1 x USB2.0;Rear panel: 1 x USB2.0, 1 x USB3.0R\$4851R\$232N/AAlarm In16-chAlarm Out4-chGENERALPower Supply12V DC/5AWorking Temperature-10 °C ~ 55 °C (14 °F ~ 131 °F)Working Humidity \leq 90% RH (non-condensing)Power Consumption (without HDD) \leq 3.15Kg (6.94lb)	SATA	4 SATA Interfaces	
Network Interface2 RJ45 10M/100M/1000M self-adaptive Ethernet InterfaceUSBFront: 1 x USB2.0;Rear panel: 1 x USB2.0, 1 x USB3.0RS4851RS232N/AAlarm In16-chAlarm Out4-chGENERALPower SupplyPower Supply12V DC/5AWorking Temperature-10 °C ~ 55 °C (14 °F ~ 131 °F)Working Humidity \leq 90% RH (non-condensing)Power Consumption (without HDD) \leq 3.15Kg (6.94lb)	Capacity		
USBFront: 1 x USB2.0;Rear panel: 1 x USB2.0, 1 x USB3.0RS4851RS232N/AAlarm In16-chAlarm Out4-chGENERALPower Supply12V DC/5AWorking Temperature-10 °C ~ 55 °C (14 °F ~ 131 °F)Working Humidity \leq 90% RH (non-condensing)Power Consumption (without HDD) \leq 3.15Kg (6.94lb)	EXTERNAL INTERFACE		
RS4851RS232N/AAlarm In16-chAlarm Out4-chGENERALPower Supply12V DC/5AWorking Temperature-10 °C ~ 55 °C (14 °F ~ 131 °F)Working Humidity \leq 90% RH (non-condensing)Power Consumption (without HDD) \leq 3.15Kg (6.94lb)	Network Interface	2 RJ45 10M/100M/1000M self-adaptive Ethernet Interface	
RS232N/AAlarm In16-chAlarm Out4-chGENERALPower Supply $12V DC/5A$ Working Temperature $-10 \ ^{\circ}C \sim 55 \ ^{\circ}C (14 \ ^{\circ}F \sim 131 \ ^{\circ}F)$ Working Humidity $\leq 90\% RH (non-condensing)$ Power Consumption (without HDD) $\leq 3.15Kg (6.94lb)$	USB	Front: 1 x USB2.0;Rear panel: 1 x USB2.0, 1 x USB3.0	
Alarm In 16-ch Alarm Out 4-ch GENERAL 90wer Supply Power Supply 12V DC/5A Working Temperature -10 °C ~ 55 °C (14 °F ~ 131 °F) Working Humidity ≤ 90% RH (non-condensing) Power Consumption (without HDD) ≤ 20W Weight (without HDD) ≤ 3.15Kg (6.94lb)	RS485	1	
Alarm Out 4-ch GENERAL 12V DC/5A Working Temperature -10 °C ~ 55 °C (14 °F ~ 131 °F) Working Humidity ≤ 90% RH (non-condensing) Power Consumption (without HDD) ≤ 20W Weight (without HDD) ≤ 3.15Kg (6.94lb)	RS232	N/A	
GENERAL 12V DC/5A Power Supply 12V DC/5A Working Temperature -10 °C ~ 55 °C (14 °F ~ 131 °F) Working Humidity ≤ 90% RH (non-condensing) Power Consumption (without HDD) ≤ 20W Weight (without HDD) ≤ 3.15Kg (6.94lb)	Alarm In	16-ch	
Power Supply 12V DC/5A Working Temperature -10 °C ~ 55 °C (14 °F ~ 131 °F) Working Humidity ≤ 90% RH (non-condensing) Power Consumption (without HDD) ≤ 20W Weight (without HDD) ≤ 3.15Kg (6.94lb)	Alarm Out	4-ch	
Working Temperature $-10 ^{\circ}\text{C} \sim 55 ^{\circ}\text{C} (14 ^{\circ}\text{F} \sim 131 ^{\circ}\text{F})$ Working Humidity $\leq 90\% \text{RH} (\text{non-condensing})$ Power Consumption (without HDD) $\leq 20W$ Weight (without HDD) $\leq 3.15 \text{Kg} (6.94 \text{lb})$	GENERAL		
Working Humidity \$\le 90\% RH (non-condensing) Power Consumption (without HDD) \$\le 20W Weight (without HDD) \$\le 3.15Kg (6.94lb)	Power Supply	12V DC/5A	
Power Consumption (without HDD) ≤ 20W Weight (without HDD) ≤ 3.15Kg (6.94lb)	Working Temperature	-10 °C ~ 55 °C (14 °F ~ 131 °F)	
(without HDD) ≤ 20W Weight (without HDD) ≤ 3.15Kg (6.94lb)	Working Humidity	\leq 90% RH (non-condensing)	
	Power Consumption (without HDD)	≤ 20W	
Dimensions 440mm × 344mm × 48mm (17.3"×13.5"×1.9")	Weight (without HDD)	≤ 3.15Kg (6.94lb)	
	Dimensions	440mm \times 344mm \times 48mm (17.3" \times 13.5" \times 1.9")	

Dimensions:



PRO SERIES VPRO-NVR-32-4H-U

32 Channel Network Video Recorder with 4HDD



Panels:

