

PRO SERIES VPRO-NVR-64RR-8H-U

64 Channel Network Video Recorder with 8HDD with RAID



Features:

- Support Ultra 265/H.265/H.264 video formats
- 64-channel input
- Support mainstream cameras of ONVIF conformance(Profile S, Profile G, Profile T) and RTSP protocols
- Support 2 HDMI and 2 VGA. VGA1 and HDMI1 simultaneous output, VGA2 and HDMI2 simultaneous output. VGA1/HDMI1 and VGA2/HDMI2 independent output
- Up to 32 Megapixels resolution recording
- 8 SATA HDD, up to 16TB for each HDD Support N+1 Hot spare
- Support HDD hot swap with RAID 0, 1, 5, 6, 10 storage scheme configurable
- ANR technology to enhance the storage reliability when the network is disconnected
- Redundant power supply optional
- Support cloud upgrade

Specifications:

| VIDEO/AUDIO INPUT | |
|------------------------------------|--|
| IP Video Input | 64-ch |
| Audio Input | 1-ch, RCA |
| NETWORK | |
| Incoming bandwidth | 384Mbps |
| Outgoing bandwidth | 384Mbps |
| Remote Users | 128 |
| Protocols | TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SNMP, SMTP, NFS, RTSP, 802.1x, IPV6 |
| Browser | IE(IE10/11) for Windows Firefox (version 52.0 and above) for Windows Chrome (version 45 and above) for Windows Edge(version 79 and above) for Windows |
| VIDEO/AUDIO OUTPUT | |
| HDMI/VGA Output | HDMI1, HDMI2: 4K (3840x2160)@60, 4K (3840x2160)@30, 1920x1080p@60, 1920x1080p@50, 1600x1200@60, 1280x1024@60,1280x720@60, 1024x768@60 VGA1, VGA2: 1920x1080p@60, 1920x1080p@50, 1600x1200@60, 1280x1024@60, 1280x720@60, 1024x768@60 |
| Recording Resolution | 32MP/16MP/12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF |
| Audio Output | 2-ch, RCA |
| Two-way Audio | 1-ch, RCA(Using the audio input and output) |
| Audio Compression | G.711A, G.711U |
| Synchronous Playback | 16-ch |
| Live View Display | HDMI1, VGA1: 1/4/6/8/9/16/25/36/64 HDMI2, VGA2: 1/4/6/8/9/16/25/36 |
| Corridor Mode Screen | 3/4/5/7/9/10/12/16/32 |
| SNAPSHOT | |
| FTP/Schedule/Event Snapshot | 16-ch snapshot, up to 1080P resolution |
| DECODING | |
| Decoding Format | Ultra 265/H.265/H.264 |
| Live View/Playback | 32MP/12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF |
| Capability | 2 x 32MP@30, 4 x 16MP@30, 5 x 12MP@30, 8 x 4K@30, 16 x 4MP@30, 32 x 1080P@30, 54 x 960P@25, 72 x 720P@30, 128 x D1 |
| HARD DISK | |
| SATA | 8 SATA interfaces |
| Capacity | Up to 16TB for each disk |
| Disk Group | Support |
| Disk Array Type | RAID 0/1/5/6/10 |
| Hot Swap | Supp |

PRO SERIES VPRO-NVR-64RR-8H-U


64 Channel Network Video Recorder with 8HDD with RAID



VEILUX
The Art of Surveillance

| SMART | |
|--------------------------------|---|
| VCA Detection by Camera | Face Detection;Vehicle Detection;SIP(Intrusion Detection, Cross Line Detection, Enter Area, Leave Area);Ultra Motion Detection(UMD);Temperature Detection(Fire Detection, Smoking Detection, Temperature Measurement, Smoke and Fire Detection);People Counting(People Flow Counting, Crowd Density Monitoring);Video Metadata;Traffic Monitoring |
| VCA Search | Motor Vehicle Search, Non-Motor Vehicle Search, Human Body Search, General Search, People Counting Report, Heat Map |
| Smart by IPC | All channels (up to 16 images/s in total)Face Detection, Vehicle Detection, Temperature Detection, SIP, UMD, Video Metadata, Traffic Monitoring |
| Vehicle Picture Library | Up to 5 vehicle picture libraries, with up to 25,000 vehicle pictures in total |
| ALARM | |
| General Alarm | Defocus Detection, Scene Change Detection, Object Left Behind, Object Removed, Auto Tracking, Motion, Tampering, Human Body Detection, Video Loss, Alarm Input, Audio Detection |
| Alert Alarm | IP Conflict, Network Disconnected, Disk Offline, Disk Abnormal, Illegal Access, Hard Disk Space Low, Hard Disk Full, Recording/ Snapshot Abnormal |
| EXTERNAL INTERFACE | |
| Network Interface | 2 RJ-45 10M/100M/1000M self-adaptive Ethernet Interface |
| USB Interface | Front: 2 x USB2.0, Rear panel: 2 x USB3.0 |
| eSATA | 1 |
| RS232 | 1 |
| RS485 | 1 |
| Alarm In | 16-ch |
| Alarm Out | 10-ch |
| GENERAL | |
| Power Supply | 100~240V AC Power Consumption: ≤ 50W (without HDD) |
| Power Output | 12V |
| Working Environment | -10°C~+ 55°C (+14°F~+131°F), Humidity ≤ 90% RH (non-condensing) |
| Dimensions (LxWxH) | 442mm × 448mm × 93mm (17.6" × 17.4" × 3.7") |
| Weight | ≤ 6Kg (13.23lb) |

Dimensions



Rear Panel

