

VR-5B-16S-2H

16 Channel Digital Video Recorder with 2 HDD



Features:

- 16-channel BNC input
- Up to 5MP resolution for recording
- Holds up to 2x HDD
- H.265, H.264 video compression
- Supports ONVIF
- 2 x USB 2.0
- RS485 - Terminal Block

Specifications:

VIDEO	
Video Input	16 BNC
Input Resolution	5MP, 4MP, 3MP, 2MP, 960H
Output	1 HDMI , 1 VGA , 1 D-SUB
Output Resolution	UHD, QHD, FHD, SXGA, XGA
RECORDING	
Speed	2MP : 15fps/ch 5MP 4MP 3MP : 15fps/ch (*Half Resolution)
Compression	H.264, H.265
Resolution	5MP, 4MP, 3MP (*Half Resolution) / 2MP, 960H
AUDIO	
Input	8 RCA + 8 D-SUB
Output	1 HDMI, 1 RCA
INTERFACE	
Sensor In/Out	16 / 1 - NC / NO
USB	2 x USB 2.0
PTZ/Keyboard	RS485 - Terminal Block
ATM /POS	Ethernet POS
NETWORK	
Interface	Ethernet 10/100/1G
Compression	H.264, H.265
Speed	10fps (5MP), 15fps (2MP)
Resolution	Normal 2MP, REC Video Bypass Max. 5MP(Half)
SYSTEM	
OS	Embedded Linux (Built-in Flash Memory)
Pre/Post-Alarm	5sec / 5sec~5min
Recording Mode	Continuous, Event, Schedule
Data Search	Calendar, Multi Day / Time, Event, Go to Time
Backup Interface	USB, Network
Backup Type	Video (RMS, AVI), Capture(JPEG), Log List, Setup Data
Alarm Action	Buzzer, PTZ Preset, E-mail , SPOT, Relay, Event Popup, Push
User	15 Users (Admin, User1 ~ User14)
Network Viewer	NETUS-Pro(CMS), Web Viewer, Mac Viewer, NETUS-Eyes(iOS, Android)
ONVIF	ONVIF Profile T
STORAGE	
Primary	2 HDD bays
GENERAL	
Size (Lx W x H)	430mm x 270mm x 86mm (17" x 10.63" x 3.4")
Weight (w/o HDD)	4Kg (8.80lb)
Temp / Humidity	5 ~ 40 ° / 10 ~ 80%
Power Supply	12V / 5A
Power Consumption	60 Watts