

# V-RECON SERIES VS-2HD-TVI

2.4 Megapixel TVI Box Camera



Specifications	
Image Sensor	1/2.8" 2.4 Mega Pixel SONY CMOS Sensor
Scanning system	Progressive
Resolution	Digital : 1920Hx1080P, Analog : 1280H NTSC/PAL CVBS
Total Pixels	2000(H) x 1241(V) = 2.48 M pixel
Active pixels	1984(H) x 1225(V) = 2.43 M pixel
Shutter Speed	Auto / Manual (1/50(1/60)~1/50,000)
Min. Illumination	Color : 1.0 lux , BW : 0.5lux
S/N Ratio	>50dB (AGC off)
AGC	Off / Low / Min / High
Day & Night	Auto / Color / B&W / Ext
White Balance	ATW / Manual / AWC Push
Backlight	Off / BLC / HLI / D-WDR / XDR
Mirror	Off / H / V / H&V / Rotate
XDR	Auto / Manual 0~10
DNR	Off / Low / Middle / High
Privacy	4 masks
Motion	Off / On (4 area)
LSC	On / Off
Language	English, Chinese, German, French, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish
Day & Night System	ICR
Video Output	TVI, CVBS
Power Consumption	DC12V 1250m A
Operating Temperature	-10°C ~ 50°C (Humidity: 0%RD ~ 80%RH)
Storage Temperature	-20°C ~ 60°C (Humidity: 0%RD ~ 80%RH)
Dimensions (mm)	61(W) x 55(H) x 106(L)
Weight	460g



## Key Features

- 1/2.8 2.4 Mega Pixel SONY CMOS
- HD Resolution:
  - Digital: TVI 1080P 30fps
  - Analog: CVBS 1280H NTSC/PAL
- XDR, D-WDR (Digital Noise Reduction)
- Privacy Mask Function
- Motion Detection
- True Day & Night (ICR)
- Video Output -TVI, CVBS
- External Control (Focus/Zoom, OSD)
- Service Video Controller through Cable

## Accessories



- Outdoor/Indoor Camera Housing
- VCH-619
  - VCH-619HB
  - VCH-619HBIR



- Lens
- VL-3M2812