

# VV-4HDIR30-4IN1-Q

4MP Varifocal Dome Camera with up to 30m IR and 4-in-1 signal



## Features

- 4MP Varifocal Dome camera
- D-WDR, 2DNR
- 3.3-12mm Varifocal Lens
- 30 m IR distance
- Water and dust resistant (IP67)
- 4-in-1 (4 signals switchable TVI/AHD/CVI/CVBS)

## Specifications

CAMERA	
<b>Image Sensor</b>	1/2.7" CMOS Sensor
<b>Signal System</b>	PAL/NTSC
<b>Effective Pixels</b>	2560 (H) x 1440 (V)
<b>Electronic Shutter</b>	AUTO/ 1/50 (1/60) - 1/50,000sec
<b>Min. Illumination</b>	0.01 Lux@(F1.2, AGC ON), 0LUX with IR
<b>Video Frame Rate</b>	PAL/NTSC: 4MP@20fps
<b>Video Output</b>	AHD/TVI/CVI/CVBS
CAMERA FEATURES	
<b>S/N Ratio</b>	≥50dB
<b>Noise Reduction</b>	2D DNR
<b>Day &amp; Night</b>	EXT/Auto/Color/B&W
<b>White Balance</b>	ATW/Manual
<b>WDR</b>	D-WDR
<b>IR LED</b>	4pcs SMD LED
<b>IR Range</b>	30m
LENS	
<b>Focal Length</b>	3.3-12mm Manual Zoom Lens
<b>Angle of View</b>	Horizontal FOV: 102~38°, Vertical FOV: 56~22°, Diagonal FOV: 118~42°
<b>Lens Type</b>	Fixed Iris
<b>Mount Type</b>	Ø14
GENERAL	
<b>IP Rating</b>	IP67
<b>Housing Material</b>	Metal
<b>Power Supply</b>	DC12V(±10%)
<b>Power Consumption</b>	< 8W
<b>Working Temperature</b>	-40°C ~ 60°C
<b>Humidity</b>	RH95% MAX
<b>Dimensions</b>	Ø 142 x 113.4 (mm)
<b>Weight</b>	770g

## Specifications

