


V-RECON SERIES VV-5HDIR24Z-4N1-S

5MP High Resolution Vandal Proof IR Motorized Dome Camera



Key Features

- 1/2.8" 5MP Sony CMOS Sensor
- Lens: Equipped with 3 Axis Lens
- Motion Detection
- Privacy Mask Function
- 2.8-12mm TDN DC Iris Motorized Lens
- True Day & Night (ICR)
- Video Output: AHD / TVI / CVI / CVBS
- Built-in IR LED 24pcs (Night View Distance up to 30m)
- External Control (Focus / Zoom, OSD)
- Service Video Controller through Cable
- Transmission Distance: Up to 200m via Coaxial Cable (RG59)

Specifications	
Image Sensor	1/2.8" 5MP Sony CMOS Sensor
Scanning System	Progressive
Resolution	2560 x 1944 PAL/NTSC
Video Out	AHD: 5M20fps, 5M12.5fps, 4M25/30fps, 4M15fps, 2M25/30fps TVI: 5M20fps, 5M12.5fps, 4M25/30fps, 4M15fps, 2M25/30fps CVI: 4M25/30fps, 2M25/30fps CVBS: PAL/NTSC
Active Pixels	2560 x 1944 NTSC
Shutter Speed	Auto/ Manual (1/50(1/60) ~ 1/100,000)
Min. Illumination	0.003 Lux (Color) (0 Lux IR LED ON)
S/N Ratio	>50dB (AGC off)
AGC	1- 5 Levels
Day & Night	Auto/ Color/ B&W/ Ext
White Balance	ATW/ Manual/ AWC Push
Backlight	1 - 16 Levels
Mirror	Off/ H/ V/ H&V/ Rotate
HLC	On/ Off
OSD Control	Include OSD Control
Picture Functions	D-WDR, HSBLC, 3DNR, Defog
Privacy Zone	4 Areas
Motion Detection	4 Areas
LSC	On/ Off
Day & Night System	ICR Function
Video Output	AHD/ TVI/ CVI/ CVBS
IR Led	24 Units
Night View Distance	up to 30m
Lens	2.8-12mm TDN DC Iris Motorized Lens
Power Consumption	DC12V Less than 150mA
Temperature Operating	14°F to 131°F (-10°C to 55°C)
Temperature Storage	-4°F to 140°F (-20°C to 60°C)
Operating Humidity	10% - 85% RH
IP Rating	IP66
Dimensions (WxDxH)	Ø5.1" x 4.7" (H) [Ø13cm x 12cm(H)]
Unit Weight	1.90 lb (0.861 kg)
Shipping Weight	2.15 lb (0.975 kg)
Certificates	CE, FCC