

# PRO SERIES VVT-2MIR25SL

2.0MP IR Metal Dome HD Camera with Starlight



## Key Features

- 4-in-1 vandal dome Camera
- 1/2.8"IMX307 CMOS 2.0M+FH8550M
- 12pcs SMD LEDs,
- 15m IR Range
- Standard match 2.8mm lens
- With WDR, starlight
- Default TVI output

## Specifications

CAMERA	
<b>Power System</b>	NTSC
<b>Sensor</b>	IMX307 1/2.8
<b>DSP</b>	FH8550M
<b>Active Pixel</b>	1920*1080
<b>Sync.</b>	Internal
<b>Resolution</b>	1080P
<b>Video Out</b>	A/C/T/CVBS
<b>Minimum Illumination</b>	0.0001Lux(F1.2)
<b>Gama Adjust</b>	0.45
<b>AF Mode</b>	SEMI/AUTO/MANUAL
<b>Electric Shutter</b>	1/30s-1/10000s
<b>S/N Ratio</b>	50dB(min)
<b>AE</b>	GLOBE/BLC
<b>WB</b>	ATW/MWB
<b>WDR</b>	EXT/OPEN/CLOSE
<b>3DNR</b>	AUTO/MANUAL(0-30)
<b>OSD</b>	Yes
<b>Language</b>	Eng Chin1/2 Russ Ital Spain Franc POL Port JAPA
<b>Day/Night</b>	Auto, Color, B/W, Ext
<b>Power Input</b>	DC12V±1V
<b>Power Dissipation</b>	95mA-105mA
<b>Transmission distance</b>	75-5 300M
<b>Operation Temperature</b>	Temperature -10°C+55°C, Humidity less than 85%RH
<b>Weight</b>	0.7KG
<b>Color</b>	Off white